

# THE ULTIMATE THIN CLIENT SOLUTION WITH AMAZING PERFORMANCE ON GREEN TECHNOLOGY REVOLUTION



Home =

Intro 🗆

**Benefits** 

Manages

Specs

Interface

Compare





# INTRODUCTION

Compared to traditional PC, Thin Client can benefit enterprise users with higher IT management efficiency, productivity and lower TCO.

SMARTSTATION Thin Client is the smallest, most advanced thin client on the market. It combines great performance, stateless operation, low power consumption, remote management and simple device setup and imaging. This small, lightweight, solid state unit can be mounted on the back of monitor, making SMARTSTATION Thin Client ideal for any space-constrained environment.

SMARTSTATION Thin Client series are available with Linux Embedded, Windows 7 Embedded, Windows 10 IOT OS.

SMARTSTATION is dedicated to be the professional thin client and embedded computing provider for over 21 years and now we are one of the top independent manufacturer of thin client. With providing design, manufacturing and service support functions for embedded computing SMARTSTATION is your best embedded solution partner to empower more efficiency and safety for your e-World.

Smart 2530 V2 Thin Clients comes with Linux Embedded Operating System with protocols like RDP 8.0, Citrix Certified HDX Ready, VM Ware VDI Client with RDP & PCOIP Support, it also comes with SEP USB redirection printing support and Multimedia Redirection, also provide support for USB Block / Allow in RDP Session, can support with 32 bit graphics. Having tool to identify network functionality. Font smoothing and Desktop Background is also supported. It can support Server Operating system Microsoft 2003, 2008, 2012, 2016, Desktop Operating System like Microsoft Windows XP, Windows 7, and Windows 8, Windows 10. It also supports Linux Environment with XRDP

Smart 2530 V2 are best suitable for Education, University, Small & Medium Scale Industries, SOHO, Hospitals, Chartered Accountants, and Traders

o m e

Intro

Benefits **E** 

Manages

Specs =

Interface **I** 

Compare





# SMARTSTATION THIN CLIENT BENEFITS

## **GREEN**

Lower power consumption for energy saving and reduce CO2 for earth saving.

Our products focus on reducing, reusing and recycling materials used in our manufacturing operations.

Our environment compliance effort including ISO 9001:2008 Certification.

## **DURABLE**

Fanless design for long life span, noise free and higher system reliability. Our thin client components are used industrial level and solid parts for long lifespan.

## **ECONOMIC**

Lower power cost of ownership (TCO): Save more than 50% off cost than using traditional desktops for energy saving and maintenance cost saving.



#### **SECURE**

Since the software becomes entirely confined to the servers, thin clients are protected from the use of unauthorized software or the introduction of viruses, Unlike PCs and traditional laptops, thin clients are locked down and offer greater security against theft, damage, malware, spyware and viruses.

Very Low	Cost	Ultra Low Power	Better Performance	Secure	Power Saver
Easy to Ma	anage	Stable & Reliable	Fanless Design	Eco Friendly	Maintenance Free

l o m e

Intro

Benefits

Manages **—** 

Specs =

Interface **I** 

Compare

# SMART CCCM Centralized Management

CCCM (Cinfin Cloud Client Management Software) supports multi-platform, multi-OS-type. Contains functions such as remote assistance, batch deployment, software dispatch, application upgrade etc. With unified management interface, to achieve centralized management and group management.

# Unified management interface, adapt to centralized management and group management.

Provides unified management interface, user account, roles (administrator privileges), resources (cloud client) separated, to achieve centralized management and group management.



## **EXCELLENT USER EXPERIENCE**

While support instant upgrade, also support automatic upgrade while cloud client shutting down or Non-working time, ensure user not be interrupted while working.

# STANDARD PROTOCOL, FULLY MANAGEMENT

The solution can manage various cloud clients with different OS (XPe/WES7/COS\*). The solution defined a standard communication interface, which is convenient to manage cross-platform device.





Smart 2530-V2

Home I

ntro

Benefits **E** 

Manages

Specs -

Interface **I** 

Compare

Contact

# SMART CCCM Centralized Management Functions

FUNCTION ITEM	FUNCTION DESCRIPTION		
System configuration	Remotely system configuration and software configuration could be set remotely, the common system configurations contain Display, Date and Time, System User, Network, Browser, Printer, Connection Item and other software configuration and template could be applied as well as application configuration could be set in batch.		
Remote Assist	Issues could be solved by remote analysis ways: Remote monitoring, Screen shot, Instant Messaging etc.		
Power Management	"Turn Off", Log Off", "Restart", "Wake up", could be done remotely and intelligently.		
Message Management	Notification or message could be sent from administrator to single cloud client or batch cloud client, and messages could be done instantly between client and server (windows).		
File Deployment	Application installation package could be dispatched fastly and installed safely, and you can copy file to client, deploy operating system or upgrade patch.		
Log Management	Record the time, content and result of the operation by administrator. It is convenient for administrator to track in the future.		
Device Security	Disable or enable peripherals.		





Smart 2530-V2

Home I

Intro 🔳

Benefits

Manages

Specs =

Interface **I** 

Compare

Contact

Specifications

Processor	CPU	ARM Cortex A9 Quad-Core 1.6 GHz	
Memory	RAM	1 GB (on board)	
Storage	eMMC	4 GB (on board)	
I/O Peripheral Support	Display Ports	VGA x 1, HDMI x 1	
	USB Ports	x 1 USB 2.0 (front), x 3 5 USB 2.0 (side)	
Networking	LAN	1 (10/100 Base-T Fast Ethernet, RJ-45)	
Display Support	Resolution	Up to 1920x1080@60Hz	
	Color Depth	Support 32bit true color	
	Dual Display	Not supported	
Audio	Front	Line-out x 1, Mic-in x 1 (1/8-inch mini jack)	
Physical Characteristics	Dimension	110 mm x 110 mm x 27mm (without mounting kit)	
	Weight	0.174 kg.	
Power	Adapter	Worldwide auto-sensing 100-240V AC, 50/60 Hz, 5v/3A DC	
	Consumption	< 6.1w	
Environment	Cooling	Fan-less Convection	
	Operating Temperature	0 to 40	
	Relative Humidity	30% to 90% non-condensing	
Mounting	VESA Bracket	VESa Mounting Kit	
	Kensignton Lock	Built-in Kensignton security slot	


# SMART STATION Thin Client Solution



Smart 2530-V2

# Connectivity







- 1. Power Button
- 2. Power Indicator light
- 3. Line Out
- 4. Mic in

- 5. USB 2.0 Port
- 6. D-Sub (VGA) Port
- 7. HDMI Port
- 8. RJ-45

- 9. +5V DC Power input
- 10. Kensington Lock Slot
- 11. Wifi Antenna port
- 12. USB 2.0 Ports

H o m e

Intro **I** 

Benefits

Manages

Specs -

Interface

Compare **E** 





Smart 2530-V2

# CONTACTS

## **SURENDRANAGAR**

2nd Floor, Manivir Complex, Vitthal Press Road, Surendranagar-363001, Gujarat, INDIA. Cell.: +91 982 420 8213 / +91 937 465 1621, E-mail: sales@smartstation.in

## AHMEDABAD

202, Manas Complex, Opp. Star India Bazar, Satellite Road, Ahmedabad-380015, Gujarat, INDIA Cell.: +91 982 420 8213 / +91 937 465 1621, E-mail: sales@smartstation.in

# HONGKONG

Unit 04, 7/F, Bright Way Tower, No. 33, Mong Kok Road, Kowloon, Hongkong, Cell.: +86 1371 4623 640, E-mail: sales1@smartstationhk.com

## U.A.E.

P O Box No 413028, Dubai, UAE

Cell: +971-528663955, E-mail: sales@smartstationme.com











©2014 The SMARTSTATION logo and references are trademarks of SMARTSTATION. Other product names mentioned herein are for identification purposes only and may be trademarks and/or registered trademarks of their respective companies. All specifications are subject to change without notice. Whilst we make every effort to ensure the accuracy of the details, specifications, models, images and benefits featured in this datasheet, we cannot be held responsible for any errors and/or omissions. If you have any queries regarding SMARTSTATION products. Some features require support by server operating system and protocol.

H o m e

Intro **I** 

Benefits **E** 

Manages **—** 

Specs =

Interface **I** 

Compare **E**